

## Specifications of PVC Suction Hose

Inner Diameter		Thickness	Length/Roll	Weight	Working Pressure (23°C)	
inch	mm	mm	m	kg/m	bar	psi
3/4	19	2.5	50	0.25	8	120
		3	50	0.28	9	135
1	25	2.5	50	0.32	8	120
		3	50	0.35	9	135
1 1/4	32	3	50	0.4	8	120
		4	50	0.55	9	135
1 1/2	38	3	50	0.55	6	90
		4	50	0.7	7	105
2	50	4	50	0.92	6	90
		5	50	1.1	7	105
2 1/2	63	3.5	30	0.95	5	75
		4.5	30	1.23	6	90
3	75	4	30	1.45	4	60
		5	30	1.65	5	75

4	100	5	30	2.3	4	60
		6	30	2.9	5	75
5	127	6	20	3.3	4	60
		8	20	4.7	5	75
6	152	7	20	5	4	60
		9	20	6.3	5	75
8	200	7	10	6.3	4	60
		8	10	7	4	60
10	250	8	10	10	4	60
		9	10	11	4	60
12	305	12	10	18	4	60
14	355	12	10	20	4	60

## The features of PVC Spiral Helix Water Oil Suction Hose

The PVC Spiral Helix Water Oil Suction Hose boasts several distinctive features. Firstly, its spiral helix reinforcement design ensures superior durability and pressure resistance, making it suitable for demanding applications. Secondly, the hose's PVC material guarantees excellent flexibility, allowing it to adapt to various terrains and curves. Furthermore, its high suction capacity ensures efficient and smooth liquid transfer, whether it's water or oil. Additionally, the hose is

lightweight and easy to install, saving time and effort. Finally, its resistance to abrasion and corrosion ensures long-term reliability and performance. These characteristics make the PVC Spiral Helix Water Oil Suction Hose an ideal choice for various liquid transportation needs

With its remarkable durability, flexibility, water and oil suction capacity, lightweight and easy installation, as well as abrasion and corrosion resistance, the PVC spiral helix reinforced water and oil suction hose has become a leader in the field of liquid transportation. Whether in the industrial, agricultural, or other fields, it can provide users with efficient and reliable liquid transportation solutions.